

## Technical Data Sheet

**Description : ALMALEN RC (reclosable)**

**Product : PP-RC-PP**

**Color : opaque, transparent, colored**

Sheet specifications		Roll and packing specification	
Thickness:	0.25 - 2.30 mm	Core diameter:	3, 6, 8 inches
Width:	300 - 1200 mm	Sealing layer:	PP inside/outside
Density (DIN 53365):	0,910 +/- 0,020 g/cm <sup>3</sup>	Roll labelling:	1 into each core 1 on each roll
Grammage:	0.94 g/m <sup>2</sup>	Splice/reel:	max. 1 per reel
Sealing layer:	PP RC PP	Roll packaging:	PE sheet
WVTR*:	≤ 0.5 g/m <sup>2</sup> /24h	Pallet packing:	PE stretch
Modulus (DIN 53457):	l: 1100 - 1700 N/mm <sup>2</sup> q: 1000 - 1600 N/mm <sup>2</sup>	Pallet labelling:	1 on each pallet
Utilisation range:	5°C to 125°C		

### Chemical properties

Contact with fat and oil: suitable

### Possible applications

- MAP (modified atmosphere packaging) for fresh pasta, meat, poultry, fish, etc.
- Dessert packaging
- Cheese packaging
- Fast-food packaging
- Biscuit trays
- All dairy packaging

### Functional

Very good thermoforming properties

### Environment

This material is recyclable

PCR (Post-Consumer Recycled Plastic)

PIR (Post-Industrial Recycled Plastic)